

**2S ONLY**

**INTERNATIONAL FEDERATION OF MODEL AUTO RACING**

**Batteries received by IFMAR for approval, from 2013. NOTE: Batteries shown on lists: 2010 - 2012 are also allowed.**

IFMAR rules do not limit capacity or power output of batteries. Values below are Manufacturers data. -- Packs factory sealed (glue, weld etc).

Battery packs must be able to be disconnected within the Car quickly without the use of tools. Direct soldering is not allowed.

**It is essential that batteries on this list are charged using a 1S or 2S LiPo compatible charger.** It is advisable to restrict charge rates to 1C.

**It is strictly NOT ALLOWED, to charge Lithium Batteries to give an output voltage exceeding :-**

2S LiPo - 8.40v. 2S LiFe - 7.40v.

**Closed LiPo 'Sack' must be used when charging.**

**2019 IFMAR PRODUCTS LIST -- 2S Stick and 2S Saddle Lithium Batteries. 01.01.20**

**BATTERIES ON THIS HOMOLOGATION LIST HAVE BEEN CERTIFIED FOR COMPLIANCE WITH UN38.3, TESTS T1-T8.**



Submitted by:	Label Details, Part #	Illustration only	Manufacturer Supplied Data.	IFMAR measured Specification,	Approval Date
---------------	-----------------------	-------------------	-----------------------------	-------------------------------	---------------

**BATTERIES BELOW THIS LEVEL ARE APPROVED BY IFMAR FOR 2020 WORLD CHAMPIONSHIP EVENTS.**

**2S LiPo STICK BATTERIES**









Associated Electrics	Reedy Zappers # 27345		Reedy LiPo 2S 7.6v. 46.0 Wh. 115C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>264/286 g.</b>	01.01.20
Freemax Technology	Arrowmax # AM 700715		Freemax Tech. LiPo 2S 7.4v. 43.7 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>238/258 g.</b>	01.01.20
Freemax Technology	Arrowmax # AM 700710		Freemax Tech. LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>258/280 g.</b>	01.01.20
Modern Creations	T/Silverback Spiral-G # G5800 1402SIND		Modern Creations LiPo 2S 7.4v. 42.9 Wh. 140C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>238/258 g.</b>	01.01.20
Muchmore Racing	Impact # MLSG-SLCG5800		Muchmore LiPo 2S 7.4v. 43.0 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>230/250 g.</b>	01.01.20
Neidhart SA	Absima # 4150009		Neidhart SA LiPo 2S 7.6v. 33.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>171/185 g.</b>	01.01.20
Neidhart SA	Absima # 4150007		Neidhart SA LiPo 2S 7.6v. 44.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>256/278 g.</b>	01.01.20
Neidhart SA	Absima # 4150008		Neidhart SA LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>209/227 g.</b>	01.01.20
Neidhart SA	Absima # 4150006		Neidhart SA LiPo 2S 7.6v. 63.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>300/324 g.</b>	01.01.20
Neidhart SA	Orion V-Max # ORI 14522		Neidhart SA LiPo 2S 7.6v. 28.9 Wh. 128C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>138/150 g.</b>	01.01.20













Neidhart SA	Orion V-Max # ORI 14523		Neidhart SA LiPo 2S 7.6v. 31.9 Wh. 128C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>170/184 g.</b>	01.01.20
Neidhart SA	Orion V-Max # ORI 14524		Neidhart SA LiPo 2S 7.6v. 47.1 Wh. 128C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>202/218 g.</b>	01.01.20
Neidhart SA	Orion V-Max # ORI 14525		Neidhart SA LiPo 2S 7.6v. 54.7 Wh. 128C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>265/287 g.</b>	01.01.20
Neidhart SA	Orion V-Max # ORI 14526		Neidhart SA LiPo 2S 7.6v. 62.3 Wh. 128C Max charge rate: 3C 4 x 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>307/333 g.</b>	01.01.20
Neidhart SA	Performa # PA9374		Neidhart SA LiPo 2S 7.6v. 33.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>170/184 g.</b>	01.01.20
Neidhart SA	Performa # PA9373		Neidhart SA LiPo 2S 7.6v. 47.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>264/286 g.</b>	01.01.20
Neidhart SA	Performa # PA9372		Neidhart SA LiPo 2S 7.6v. 63.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>281/305 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C40002S1P HC61-HV		GensAce LiPo 2S 7.6v. 30.4 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>120/130 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C51002S2P HC65-HV		GensAce LiPo 2S 7.6v. 38.8 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>204/220 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C58002S1P HC56-HV		GensAce LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>216/234 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C60002S2P HC57-HV		GensAce LiPo 2S 7.6v. 45.6 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>264/286 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C66002S1P HC57-HV		GensAce LiPo 2S 7.6v. 50.2 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>269/291 g.</b>	01.01.20
Shenzhen Grepow	GensAce Redline # 130C82002S1P HC58-HV		GensAce LiPo 2S 7.6v. 62.3 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>286/310 g.</b>	01.01.20
United Sino Enterprises	ORCA Infinite X # LP19IN2S60T		United Sino Ent. LiPo 2S 7.4v. 44.4 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>239/259 g.</b>	01.01.20

United Sino Enterprises	ORCA Infinite X # LP19IN2S65T		United Sino Ent. LiPo 2S 7.4v. 48.1 Wh. 130C Max charge rate: 1C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0006		3-Circles LiPo 2S 7.4v. 31.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>182/198 g.</b>	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0004		3-Circles LiPo 2S 7.4v. 38.5 Wh. 110C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JD0002		3-Circles LiPo 2S 7.4v. 38.5 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>235/255 g.</b>	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0001		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>270/292 g.</b>	01.01.20
Xiamen 3-Circles	Sunpadow Platin # JA0003		3-Circles LiPo 2S 7.4v. 60.7 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>304/330 g.</b>	01.01.20



**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2019 AND ARE ALLOWED AT 2020 EVENTS.**

**2S LiPo STICK BATTERIES**

Associated Electrics	Reedy Zappers # 27338		Reedy LiPo 2S 7.6v. 32.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	28.02.19
Associated Electrics	Reedy Zappers # 27336 (Was # 27323)		Reedy LiPo 2S 7.6v. 45.0 Wh. 80C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>207/225 g.</b>	28.02.19
Intellect Battery	IP # BG2S5000HV4		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	28.02.19
Intellect Battery	IP # BG2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>207/225 g.</b>	28.02.19
Intellect Battery	IP # CC2S6000HV4		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	28.02.19
Intellect Battery	IP # CC2S7000HV4		Intellect LiPo 2S 7.6v. 53.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	28.02.19
Intellect Battery	IP # CC2S7600HV4		Intellect LiPo 2S 7.6v. 58.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>293/317 g.</b>	28.02.19
Intellect Battery	IP # CC2S8400HV4		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>317/343 g.</b>	28.02.19

LRP	LRP G3 Modified # 430273		LRP LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	28.02.19
LRP	LRP G3 Modified # 430286		LRP LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>175/189 g.</b>	28.02.19
LRP	LRP G3 Stock spec # 430285		LRP LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>211/229 g.</b>	28.02.19
Muchmore Racing	Impact # MLSG-STLGHV3800		Muchmore LiPo 2S 7.6v. 28.9 Wh. 130C Max charge rate: 1C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>181/197 g.</b>	28.02.19
Nosram	Nosram G3 Modified # 999553		Nosram LiPo 2S 7.6v. 29.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	28.02.19
Nosram	Nosram G3 Modified # 999560		Nosram LiPo 2S 7.6v. 34.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>175/189 g.</b>	28.02.19
Nosram	Nosram G3 Stock Spec # 999559		Nosram LiPo 2S 7.6v. 44.1 Wh. 130C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>211/229 g.</b>	28.02.19
Neidhart SA	Performa # PA9304		Neidhart SA LiPo 2S 7.4v. 27.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>124/134 g.</b>	28.02.19
Neidhart SA	Performa # PA9305		Neidhart SA LiPo 2S 7.6v. 30.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>126/136 g.</b>	28.02.19
Neidhart SA	Performa # PA9306		Neidhart SA LiPo 2S 7.4v. 43.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	28.02.19
Neidhart SA	Performa # PA9307		Neidhart SA LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>204/222 g.</b>	28.02.19
Process Measurement & Analysis	Optipower # OPR 28002S100B		Optipower LiPo 2S 7.4v. 20.7 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>124/134 g.</b>	28.02.19
Process Measurement & Analysis	Optipower # OPR 33002S100B		Optipower LiPo 2S 7.4v. 24.4 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>141/153 g.</b>	28.02.19
Process Measurement & Analysis	Optipower # OPR 40002S-B		Optipower LiPo 2S 7.4v. 28.8 Wh. 60C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	28.02.19

ProTek RC	ProTek RC # PTK-5100-19		ProTek LiPo 2S 7.6v. 27.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	28.02.19
ProTek RC	ProTek RC # PTK-5124-19		ProTek LiPo 2S 7.6v. 31.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	28.02.19
ProTek RC	ProTek RC # PTK-5102-19		ProTek LiPo 2S 7.6v. 37.2 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>195/211 g.</b>	28.02.19
ProTek RC	ProTek RC # PTK-5114-19		ProTek LiPo 2S 7.6v. 44.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>207/225 g.</b>	28.02.19
RC Concept	Omega # 50C5135000T		RC Concept LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>134/146 g.</b>	28.02.19
RC Concept	Omega # 50C5145000T		RC Concept LiPo 2S 7.4v. 33.3 Wh. 100C Max charge rate: 3C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>194/210 g.</b>	28.02.19
RC Concept	Omega # 50C514800000		RC Concept LiPo 2S 7.6v. 36.5 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	28.02.19
Team Corally	Corally Voltax HV # 49606		Corally LiPo 2S 7.6v. 45.6 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/224 g.</b>	28.02.19
Xiamen 3-Circles	Sunpadow # S638066		3-Circles LiPo 2S 7.4v. 28.1 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>157/170 g.</b>	28.02.19
Xiamen 3-Circles	Sunpadow # 7150135		3-Circles LiPo 2S 7.4v. 33.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>212/230 g.</b>	28.02.19
Xiamen 3-Circles	Sunpadow # S653065		3-Circles LiPo 2S 7.4v. 39.2 Wh. 130C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>243/263 g.</b>	28.02.19
Xiamen 3-Circles	Sunpadow # S684064		3-Circles LiPo 2S 7.4v. 62.2 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>325/353 g.</b>	28.02.19
Yokomo	Yokomo # YB-V235B		Yokomo LiPo 2S 7.4v. 25.9 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>151/163 g.</b>	28.02.19
Yokomo	Yokomo # YB-V246B		Yokomo LiPo 2S 7.4v. 34.0 Wh. 100C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>205/223 g.</b>	28.02.19

Yokomo	Yokomo # RPB-55LCG		Yokomo LiPo 2S 7.6v. 41.8 Wh. 140C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>232/252 g.</b>	28.02.19
Yokomo	Yokomo # RPB-60LCG		Yokomo LiPo 2S 7.4v. 44.4 Wh. 140C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/301 g.</b>	28.02.19

**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2018 AND ARE ALLOWED AT 2020 EVENTS.**

**2S LiPo STICK BATTERIES**

Associated Electrics	Reedy Zappers # 27321		Reedy LiPo 2S 7.6v. 46.0 Wh. 110C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	21.02.18
Freemax Technology	Arrowmax # AM 700706		Arrowmax LiPo 2S 7.4v. 45.9 Wh. 130C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/300 g.</b>	21.02.18
Freemax Technology	Arrowmax # AM 700105		Arrowmax LiPo 2S 7.4v. 60.7 Wh. 120C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>307/333 g.</b>	21.02.18
Intellect Battery	IP # BG2S5000HV3		Intellect LiPo 2S 7.6v. 38.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>192/208 g.</b>	21.02.18
Intellect Battery	IP # BG2S6000HV3		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/224 g.</b>	21.02.18
Intellect Battery	IP # CC2S6000HV3		Intellect LiPo 2S 7.6v. 46.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	21.02.18
Intellect Battery	IP # CC2S8400HV3		Intellect LiPo 2S 7.6v. 64.0 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>315/341 g.</b>	21.02.18
Italtrading	EZ-Power # EZP6600/2		Ital LiPo 2S 7.6v. 50.2 Wh. 140C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>264/286 g.</b>	21.02.18
LRP	LRP P5 # 430262		LRP LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>221/239 g.</b>	21.02.18
LRP	LRP P5 Stock Spec # 430261		LRP LiPo 2S 7.6v. 48.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>263/285 g.</b>	21.02.18
Modern Creations	Team Silverback Siren HV # HV64001002SINC		Modern Creations LiPo 2S 7.6v. 48.6 Wh. 100C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	21.02.18
Muchmore Racing	Impact # MLI- STLCG4300MP		Muchmore LiPo 2S 7.4v. 31.8 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>186/202 g.</b>	21.02.18

Muchmore Racing	Impact # MLI-LCG6400FD2		Muchmore LiPo 2S 7.4v. 47.4 Wh. 110C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>260/282 g.</b>	21.02.18
Muchmore Racing	Impact # MLI-MP8200FD3		Muchmore LiPo 2S 7.4v. 60.6 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>308/334 g.</b>	21.02.18
Neidhart SA	Orion Ultimate HV # ORI 14501		Orion LiPo 2S 7.6v. 26.6 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>124/134 g.</b>	21.02.18
Neidhart SA	Orion Ultimate HV # ORI 14502		Orion LiPo 2S 7.6v. 30.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>138/150 g.</b>	21.02.18
Neidhart SA	Orion Ultimate HV # ORI 14503		Orion LiPo 2S 7.6v. 44.1 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>208/226 g.</b>	21.02.18
Neidhart SA	Orion Ultimate # ORI 14514		Orion LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>253/275 g.</b>	21.02.18
Neidhart SA	Orion Ultimate HV # ORI 14505		Orion LiPo 2S 7.6v. 62.3 Wh. 120C Max charge rate: 3C 4 mm. Tubes, 4 off.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>309/335 g.</b>	21.02.18
Nosram	Nosram P5 LCG # 999548		Nosram LiPo 2S 7.6v. 41.8 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>221/239 g.</b>	21.02.18
Nosram	Nosram P5 Stock Spec # 999547		Nosram LiPo 2S 7.6v. 48.7 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>263/285 g.</b>	21.02.18
Scorpion	Platinum Series # SCPP-PS3400 BLK		Scorpion LiPo 2S 7.4v. 25.2 Wh. 65C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>131/141 g.</b>	21.02.18
Scorpion	Platinum Series # SCPP-PS6200 BLK		Scorpion LiPo 2S 7.4v. 45.9 Wh. 65C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/300 g.</b>	21.02.18
Scorpion	Platinum Series # SCPP-PS7700 BLK		Scorpion LiPo 2S 7.4v. 57.0 Wh. 65C Max charge rate: 2C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>284/308 g.</b>	21.02.18
Tianco	ORCA Gen. 4 # OBH463H4		Tianco LiPo 2S 7.6v. 47.9 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	21.02.18
Tianco	ORCA Gen. 4 # OBH485V4		Tianco LiPo 2S 7.6v. 64.6 Wh. 120C Max charge rate: 3C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>315/341 g.</b>	21.02.18

Trion	Trion # TB-STLG4300		Trion LiPo 2S 7.4v. 31.8 Wh. 120C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>184/200 g.</b>	21.02.18
Trion	Trion # TB-5000ST		Trion LiPo 2S 7.4v. 37.0 Wh. 110C Max charge rate: 2C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>205/223 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5630046		3-Circles LiPo 2S 7.4v. 22.2 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>144/156 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # H640043		3-Circles LiPo 2S 7.6v. 30.4 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>151/163 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5043126		3-Circles LiPo 2S 7.4v. 37.0 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>266/288 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5042125		3-Circles LiPo 2S 7.4v. 41.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>262/284 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5656040		3-Circles LiPo 2S 7.4v. 41.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>261/283 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5442125		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/300 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5660041		3-Circles LiPo 2S 7.4v. 44.4 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/300 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # H663026		3-Circles LiPo 2S 7.6v. 47.9 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # 5542125		3-Circles LiPo 2S 7.4v. 48.8 Wh. 120C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>294/318 g.</b>	21.02.18
Xiamen 3-Circles	Sunpadow # H684027		3-Circles LiPo 2S 7.6v. 63.8 Wh. 100C Max charge rate: 3C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>297/321 g.</b>	21.02.18

**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2017 AND ARE ALLOWED AT 2020 EVENTS.**








**2S LiPo STICK BATTERIES**

Associated Electrics	Reedy Zappers # 27310		Reedy LiPo 2S 7.6v. 28.0 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>149/161 g.</b>	11.03.17
Associated Electrics	Reedy Zappers # 27305		Reedy LiPo 2S 7.6v. 37.0 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>200/216 g.</b>	11.03.17



Associated Electrics	Reedy Zappers # 27307		Reedy LiPo 2S 44.0 Wh. 5 mm. Tubes	7.6v. 70C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>215/233 g.</b>	11.03.17
Freemax Metal Products	Arrowmax # AM 700202		Arrowmax LiPo 2S 37.0 Wh. 4 mm. Tubes.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>199/215 g.</b>	11.03.17
Freemax Metal Products	Arrowmax # AM 700203		Arrowmax LiPo 2S 45.6 Wh. 4 mm. Tubes.	7.6v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>206/224 g.</b>	11.03.17
Freemax Metal Products	Arrowmax # AM 700802		Arrowmax LiPo 2S 47.1 Wh. 5 mm. Tubes.	7.6v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>269/291 g.</b>	11.03.17
Intellect Battery	IP # LP2S3600HV2		Intellect LiPo 2S 27.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>142/154 g.</b>	11.03.17
Intellect Battery	IP # BG2S5000HV2		Intellect LiPo 2S 38.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>197/213 g.</b>	11.03.17
Intellect Battery	IP # BG2S6000HV2		Intellect LiPo 2S 46.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>216/234 g.</b>	11.03.17
Intellect Battery	IP # CC2S6000HV2		Intellect LiPo 2S 46.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>259/281 g.</b>	11.03.17
Intellect Battery	IP # CC2S8400HV2		Intellect LiPo 2S 64.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>317/343 g.</b>	11.03.17
Italtrading	EZ-Power # EZP3500/2		Ital LiPo 2S 26.6 Wh. 4 mm. Tubes	7.6v. 140C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>142/154 g.</b>	11.03.17
Italtrading	EZ-Power # EZP4900/2		Ital LiPo 2S 37.2 Wh. 4 mm. Tubes	7.6v. 140C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>197/213 g.</b>	11.03.17
LRP	LRP # 430258		LRP LiPo 2S 22.0 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>127/137 g.</b>	11.03.17
LRP	LRP # 430257		LRP LiPo 2S 26.6Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>146/158 g.</b>	11.03.17
LRP	LRP # 430256		LRP LiPo 2S 31.9 Wh. 5 mm. Tubes	7.6v. 120C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>181/196 g.</b>	11.03.17

LRP	LRP Stock Spec. # 430254		LRP LiPo 2S 7.6v. 35.0 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>196/212 g.</b>	11.03.17
LRP	LRP Stock Spec. # 430255		LRP LiPo 2S 7.6v. 45.6 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>213/231 g.</b>	11.03.17
LRP	LRP # 430252		LRP LiPo 2S 7.6v. 41.8 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>221/239 g.</b>	11.03.17
LRP	LRP Stock Spec. # 430251		LRP LiPo 2S 7.6v. 48.6 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>261/283 g.</b>	11.03.17
LRP	LRP Stock Spec. # 430250		LRP LiPo 2S 7.6v. 60.8 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>321/347 g.</b>	11.03.17
Nosram	Nosram # 999545		Nosram LiPo 2S 7.6v. 31.9 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>181/196 g.</b>	11.03.17
Nosram	Nosram # 999544		Nosram LiPo 2S 7.6v. 41.8 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>221/239 g.</b>	11.03.17
Nosram	Nosram Stock Spec. # 999543		Nosram LiPo 2S 7.6v. 48.6 Wh. 120C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>263/285 g.</b>	11.03.17
ProTek RC	ProTek RC # PTK-5100-17		ProTek LiPo 2S 7.6v. 27.4 Wh. 100C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>147/160 g.</b>	11.03.17
ProTek RC	ProTek RC # PTK-5102-17		ProTek LiPo 2S 7.6v. 37.2 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>197/213 g.</b>	11.03.17
ProTek RC	ProTek RC # PTK-5114-17		ProTek LiPo 2S 7.6v. 46.4 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>216/234 g.</b>	11.03.17
ProTek RC	ProTek RC # PTK-5115-17		ProTek LiPo 2S 7.6v. 47.9 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>259/281 g.</b>	11.03.17
ProTek RC	ProTek RC # PTK-5107-17		ProTek LiPo 2S 7.6v. 64.6 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>317/343 g.</b>	11.03.17
Scorpion	Scorpion Platinum # SCPP- PS5700-BLK		Scorpion LiPo 2S 7.4v. 42.2 Wh. 65C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>244/264 g.</b>	11.03.17

Shenzhen Grepow	GensAce # B60C46002S2P H/Case 29		GensAce LiPo 2S 34.0 Wh. 7.4v. 60C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	11.03.17
Xiamen 3-Circles	Sunpadow # 7150135		Sunpadow LiPo 2S 33.3 Wh. 7.4v. 120C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>198/215 g.</b>	11.03.17
Xiamen 3-Circles	Sunpadow # 554383		Sunpadow LiPo 2S 37.7 Wh. 7.4v. 100C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>199/216 g.</b>	11.03.17
Xiamen 3-Circles	Sunpadow # 554385		Sunpadow LiPo 2S 45.6 Wh. 7.6v. 100C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>200/217 g.</b>	11.03.17
Tianco	ORCA Gen. 3 # OBH350SP		Tianco LiPo 2S 38.0 Wh. 7.6v. 110C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	11.03.17
Tianco	ORCA Gen. 3 # OBH363R2		Tianco LiPo 2S 47.9 Wh. 7.6v. 110C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	11.03.17
Yokomo	Racing Performer # RPB-50LCG		Yokomo LiPo 2S 37.0 Wh. 7.4v. 140C 4 & 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>262/284 g.</b>	11.03.17















**2S LiPo SADDLE BATTERIES**

Intellect Battery	IP # TP2S6000HV2		Intellect LiPo 2S 2 x 3.8v. 2 x 23.0 Wh. 120C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>261/283 g.</b>	11.03.17
-------------------	------------------	---	---	---	----------

**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2016 AND ARE ALLOWED AT 2020 EVENTS.**



**2S LiPo STICK BATTERIES**

Italtrading	EZ-Power # EZP6200/2		Ital LiPo 2S 46.8 Wh. 7.4v. 60C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>303/328 g.</b>	10.01.16 Photo corrected 09.08.16
Intellect Battery	IP # CC2S3500SV1		Intellect LiPo 2S 26.0 Wh. 7.4v. 100C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>139/151 g.</b>	10.01.16
LRP	LRP # 430234		LRP LiPo 2S 41.4 Wh. 7.4v. 110C 5mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>257/279 g.</b>	10.01.16
LRP	LRP # 430232		LRP LiPo 2S 55.5 Wh. 7.4v. 110C 5mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>317/343 g.</b>	10.01.16
LRP	LRP # 430235		LRP LiPo 2S 41.4 Wh. 7.4v. 110C 5mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>242/262 g.</b>	10.01.16

LRP	LRP # 430239		LRP LiPo 2S 7.4v. 29.6 Wh. 110C 5mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>179/193 g.</b>	10.01.16
LRP	LRP # 430236		LRP LiPo 2S 7.4v. 33.3 Wh. 110C 5mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>198/214 g.</b>	10.01.16
Muchmore Racing	Impact # MLI-ST5000FD2		Muchmore LiPo 2S 7.4v. 37.0 Wh. 110C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>206/224 g.</b>	10.01.16
Nosram	Nosram X-treme Race # 999527		Nosram LiPo 2S 7.4v. 41.4 Wh. 110C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>257/279 g.</b>	10.01.16
Nosram	Nosram X-treme Race # 999525		Nosram LiPo 2S 7.4v. 55.5 Wh. 110C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>317/343 g.</b>	10.01.16
Nosram	Nosram X-treme Race # 999528		Nosram LiPo 2S 7.4v. 41.4 Wh. 110C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>242/262 g.</b>	10.01.16
Nosram	Nosram X-treme Race # 999532		Nosram LiPo 2S 7.4v. 29.6 Wh. 110C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>179/193 g.</b>	10.01.16
Nosram	Nosram X-treme Race # 999529		Nosram LiPo 2S 7.4v. 33.3 Wh. 110C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>198/214 g.</b>	10.01.16
Tianco	ORCA Infinite # OBHV63G2		Tianco LiPo 2S 7.4v. 46.6 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>271/293 g.</b>	10.01.16
Neidhart SA	Orion # ORI 14087		Orion LiPo 2S 7.4v. 42.9 Wh. 110C 4mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>254/276 g.</b>	10.01.16
Neidhart SA	ORION Carbon Pro # ORI 14066		Orion LiPo 2S 7.4v. 31.1 Wh. 100C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>198/214 g.</b>	10.01.16
Neidhart SA	Orion # ORI 14068		Orion LiPo 2S 7.4v. 33.3 Wh. 100C 5mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>197/213 g.</b>	10.01.16
Neidhart SA	Orion # ORI 14083		Orion LiPo 2S 7.4v. 37.0 Wh. 110C 4mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>204/221 g.</b>	10.01.16
Neidhart SA	Orion # ORI 14081		Orion LiPo 2S 7.4v. 23.7 Wh. 110C 4mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>125/135 g.</b>	10.01.16

Neidhart SA	Orion # ORI 14082		Orion LiPo 2S 7.4v. 28.1 Wh. 110C 4mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>146/158 g.</b>	10.01.16
Associated Electrics	Reedy # 316		Reedy LiPo 2S 7.4v. 37.0 Wh. 65C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>264/286 g.</b>	10.01.16
Associated Electrics	Reedy # 27301		Reedy LiPo 2S 7.4v. 42.0 Wh. 100C 5 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>273/295 g.</b>	10.01.16
Associated Electrics	Reedy # 321		Reedy LiPo 2S 7.4v. 45.0 Wh. 70C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>304/330 g.</b>	10.01.16
Modern Creations	Team Silverback Spiral 2 # 6400902SINC		Modern Creations LiPo 2S 7.4v. 47.3 Wh. 90C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>262/284 g.</b>	10.01.16
Vapex Technology	VP Racing # VP96412		Vapex LiPo 2S 7.4v. 45.0 Wh. 80C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>289/313 g.</b>	10.01.16
Vapex Technology	VP Racing # VP96429		Vapex LiPo 2S 7.4v. 58.0 Wh. 70C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>296/320 g.</b>	10.01.16
Vapex Technology	VP Racing # VP96436		Vapex LiPo 2S 7.4v. 39.5 Wh. 70C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>200/216 g.</b>	10.01.16
Yokomo	Racing Performer # RPB-60L		Yokomo LiPo 2S 7.4v. 44.4 Wh. 100C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>298/322 g.</b>	10.01.16
Yokomo	Racing Performer # RPB-50S		Yokomo LiPo 2S 7.4v. 37.0 Wh. 100C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>206/224 g.</b>	10.01.16
Yokomo	Racing Performer # RPB-39E2K		Yokomo LiPo 2S 7.4v. 28.8 Wh. 100C 4 mm. Tubes.	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>154/166 g.</b>	10.01.16
<b>2S LiPo SADDLE BATTERIES</b>					
Neidhart SA	Orion # ORI 14085		Orion LiPo 2S 7.4v. 29.6 Wh. 110C 4 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>184/198 g.</b>	10.01.16
<b>BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2015 AND ARE ALLOWED AT 2020 EVENTS.</b>					
<b>2S LiPo STICK BATTERIES</b>					
Associated Electrics	Reedy # 319		Reedy LiPo 2S 7.4v. 29.0 Wh. 70C	Max. dimensions : 139.0 x 47.0 x 25.1  Scrutineers Wt. allowed: - <b>157/171 g.</b>	16.02.15

Associated Electrics	Reedy # 602		Reedy LiPo 2S 7.4v. 31.0 Wh. 65C Approved 2013. Label updated. Same Spec.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>200/216 g.</b>	16.02.15
Intellect Battery	IP # CC2S6000SV1		Intellect LiPo 2S 7.4v. 44.0 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>271/293 g.</b>	16.02.15
Intellect Battery	IP # CC2S7800SV1		Intellect LiPo 2S 7.4v. 58.0 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	16.02.15
Intellect Battery	IP # BG2S5000SV1		Intellect LiPo 2S 7.4v. 37.0 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
LRP	LRP # 430221		LRP LiPo 2S 7.4v. 40.7 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>275/297 g.</b>	16.02.15
LRP	LRP # 430223		LRP LiPo 2S 7.4v. 41.4 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>261/283 g.</b>	16.02.15
LRP	LRP # 430222		LRP LiPo 2S 7.4v. 42.9 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>276/300 g.</b>	16.02.15
LRP	LRP # 430220		LRP LiPo 2S 7.4v. 51.8 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>313/339 g.</b>	16.02.15
LRP	LRP # 430228		LRP LiPo 2S 7.4v. 31.8 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>204/220 g.</b>	16.02.15
LRP	LRP # 430227		LRP LiPo 2S 7.4v. 33.3 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>204/220 g.</b>	16.02.15
LRP	LRP # 430229		LRP LiPo 2S 7.4v. 21.5 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>136/148 g.</b>	16.02.15
LRP	LRP # 430218		LRP LiPo 2S 7.4v. 19.2 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>129/139 g.</b>	16.02.15
Muchmore Racing	Impact # MLI-ST4500FD2		Muchmore LiPo 2S 7.4v. 33.3 Wh. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>197/213 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999515		Nosram LiPo 2S 7.4v. 40.7 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>275/297 g.</b>	16.02.15

Nosram	Nosram X-treme Race # 999517		Nosram LiPo 2S 41.4 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>261/283 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999516		Nosram LiPo 2S 42.9 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>276/300 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999514		Nosram LiPo 2S 51.8 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>313/339 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999522		Nosram LiPo 2S 31.8 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>204/220 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999521		Nosram LiPo 2S 33.3 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>204/220 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999523		Nosram LiPo 2S 21.5 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>136/148 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999512		Nosram LiPo 2S 19.2 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>129/139 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR55002S50B		Optipower LiPo 2S 40.7 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>288/312 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR55002S50FL		Optipower LiPo 2S 40.7 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>298/322 g.</b> Inc. wires.	16.02.15
Process Measurement & Analysis	Optipower # OPR65002S50B		Optipower LiPo 2S 48.1 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>295/319 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR65002S50FL		Optipower LiPo 2S 48.1 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>289/313 g.</b> Inc. wires.	16.02.15
Process Measurement & Analysis	Optipower # OPR70002S50B		Optipower LiPo 2S 51.8 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>300/326 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR70002S50FL		Optipower LiPo 2S 51.8 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>302/328 g.</b> Inc. wires.	16.02.15
ProTek RC	ProTek RC # PTK 5104-15		ProTek LiPo 2S 39.2 Wh. 5 mm. Tubes	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>271/293 g.</b>	16.02.15

ProTek RC	ProTek RC # PTK 5107-15		ProTek LiPo 2S 7.4v. 47.4 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	16.02.15
ProTek RC	ProTek RC # PTK 5102-15		ProTek LiPo 2S 7.4v. 31.5 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
Tianco	ORCA Infinite # OBHV62N8		Tianco LiPo 2S 7.4v. 45.9 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>271/293 g.</b>	16.02.15
Tianco	ORCA Infinite # OBHV48F7		Tianco LiPo 2S 7.4v. 35.5 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
Scorpion	Platinum Series # SCPP-PS6200		Scorpion LiPo 2S 7.4v. 45.9 Wh. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>278/302 g.</b>	16.02.15
Scorpion	Platinum Series # SCPP-PS4200		Scorpion LiPo 2S 7.4v. 31.1 Wh. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>190/206 g.</b>	16.02.15
Trion	# TB 1333		Trion LiPo 2S 7.4v. 35.5 Wh. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
Trion	# TB 1378		Trion LiPo 2S 7.4v. 35.5 Wh. 90C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
Trion	# TB 1334		Trion LiPo 2S 7.4v. 25.9 Wh. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>141/153 g.</b>	16.02.15
Yokomo	Racing Performer # RBP-58R		Yokomo LiPo 2S 7.4v. 42.9 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>263/285 g.</b>	16.02.15
Yokomo	Racing Performer # RBP-35E2		Yokomo LiPo 2S 7.4v. 25.9 Wh. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>141/153 g.</b>	16.02.15
Yokomo	Racing Performer # RBP-48S		Yokomo LiPo 2S 7.4v. 35.5 Wh. 100C 5 mm. Tubes	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>202/218 g.</b>	16.02.15
<b>2S LiPo SADDLE BATTERIES</b>					
Intellect Battery	IP # TP2S6000SV1		Intellect LiPo 2S 7.4v. 22.0 (x2) Wh. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>267/289 g.</b>	16.02.15
LRP	LRP # 430225		LRP LiPo 2S 7.4v. 40.7 Wh. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>265/287 g.</b>	16.02.15



LRP	LRP # 430226		LRP LiPo 2S 27.4 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>180/196 g.</b>	16.02.15
Muchmore Racing	Impact # MLI-IS6000FD2		Muchmore LiPo 2S 44.4 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>267/289 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999519		Nosram LiPo 2S 40.7 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>265/287 g.</b>	16.02.15
Nosram	Nosram X-treme Race # 999520		Nosram LiPo 2S 27.4 Wh.	7.4v. 110C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>180/196 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR500050BSD		Optipower LiPo 2S 37.0 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>271/293 g.</b>	16.02.15
Process Measurement & Analysis	Optipower # OPR500050FLSD		Optipower LiPo 2S 37.0 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>280/304 g.</b> Inc. wires.	16.02.15
ProTek RC	ProTek RC # PTK 5112-15		ProTek LiPo 2S 38.5 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>267/289 g.</b>	16.02.15
Scorpion	Platinum Series # SCPP-PS5600		Scorpion LiPo 2S 41.4 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>250/270 g.</b>	16.02.15

**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2014 AND ARE ALLOWED AT 2020 EVENTS.**

**2S LiPo STICK BATTERIES**

Associated Electrics	Reedy # 313		Reedy LiPo 2S 52.0 Wh. 5mm. Tubes	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>305/331 g.</b>	17.02.14
Hacker Motor	Hacker Top Fuel # 77200277		Hacker LiPo 2S 50.3 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>300/325 g.</b>	17.02.14
Hacker Motor	Hacker Top Fuel # 74500277		Hacker LiPo 2S 31.1 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>199/215 g.</b>	17.02.14
Intellect Battery	IP # CC2S6000V9		Intellect LiPo 2S 44.0 Wh. 5mm. Tubes	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	17.02.14
Intellect Battery	IP # CC2S7600V9		Intellect LiPo 2S 56.0 Wh. 5mm. Tubes	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>321/348 g.</b>	17.02.14
Italtrading	EZ-Power # EZP7200/2		Ital LiPo 2S 53.0 Wh.	7.4v. 70C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>307/332 g.</b>	17.02.14

LRP VTEC	VTEC # 430211		LRP LiPo 2S 44.4 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>282/306 g.</b>	17.02.14
LRP VTEC	VTEC # 430210		LRP LiPo 2S 55.5 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>318/345 g.</b>	17.02.14
LRP VTEC	VTEC # 430214		LRP LiPo 2S 34.8 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>213/231 g.</b>	17.02.14
Muchmore Racing	Muchmore Impact # MLI- IH6000SP		Muchmore LiPo 2S 44.4 Wh.	7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>278/302 g.</b>	17.02.14
Neidhart SA	ORION Carbon Pro # ORI 14061		Orion LiPo 2S 42.9 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>296/320 g.</b>	17.02.14
Neidhart SA	ORION Carbon Pro # ORI 14059		Orion LiPo 2S 42.9 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>297/321 g.</b>	17.02.14
Neidhart SA	ORION Carbon Pro # ORI 14062		Orion LiPo 2S 50.3 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>301/327 g.</b>	17.02.14
Neidhart SA	ORION Carbon Pro # ORI 14060		Orion LiPo 2S 50.3 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>305/331 g.</b>	17.02.14
Nosram VTEC	Nosram X-treme Race # 999508		Nosram LiPo 2S 44.4 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>282/306 g.</b>	17.02.14
Nosram VTEC	Nosram X-treme Race # 999507		Nosram LiPo 2S 55.5 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>318/345 g.</b>	17.02.14
Nosram VTEC	Nosram X-treme Race # 999511		Nosram LiPo 2S 34.8 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>213/231 g.</b>	17.02.14
nVision	nVision # NVO 1120		nVision LiPo 2S 42.9 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>302/327 g.</b>	17.02.14
nVision	nVision # NVO 1118		nVision LiPo 2S 42.9 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>305/331 g.</b>	17.02.14
nVision	nVision # NVO 1121		nVision LiPo 2S 50.3 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>308/334 g.</b>	17.02.14

nVision	nVision # NVO 1119		nVision LiPo 2S 50.3 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>311/337 g.</b>	17.02.14
Pro Models BVBA	Corally # 48255		Corally LiPo 2S 59.2 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	17.02.14
ProTek RC	ProTek RC # PTK 5104-14		ProTek LiPo 2S 42.9 Wh. 5mm. Tubes	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	17.02.14
ProTek RC	ProTek RC # PTK 5107-14		ProTek LiPo 2S 54.7 Wh. 5mm. Tubes	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>321/348 g.</b>	17.02.14
Revtech Trinity Epic	RevTech FormulaX # REV2021-5		Revtech LiPo 2S 52.9 Wh. 5mm. Tubes	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>298/322 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B65C50002S2 PH/Case10		Acepow LiPo 2S 37.0 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>282/306 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B65C50002S1 PH/Case42		Acepow LiPo 2S 37.0 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>273/295 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B65C53002S1 PH/Case10		Acepow LiPo 2S 39.2 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>290/314 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B45C58002S2 PH/Case10		Acepow LiPo 2S 42.9 Wh.	7.4v. 45C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>293/317 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B50C65002S1 PH/Case10		Acepow LiPo 2S 48.1 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>285/309 g.</b>	17.02.14
Team Powers	Team Powers # TP720075C2S		RC Explorer LiPo 2S 55.0 Wh.	7.4v. 75C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>307/332 g.</b>	17.02.14
Tianco	ORCA Infinite # OB6290G6		Orca LiPo 2S 45.9 Wh. 5mm. Tubes	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	17.02.14
Tianco	ORCA Infinite # OB7590GT		Orca LiPo 2S 55.5 Wh. 5mm. Tubes	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>322/348 g.</b>	17.02.14
<b>2S LiPo SADDLE BATTERIES</b>						
Hacker Motor	Hacker Top Fuel # 75700278		Hacker LiPo 2S 40.7 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>277/300 g.</b>	17.02.14

LRP VTEC	VTEC # 430213		LRP LiPo 2S 42.9 Wh. 7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>267/289 g.</b>	17.02.14
Nosram VTEC	Nosram X-treme Race # 999510		Nosram LiPo 2S 42.9 Wh. 7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>267/289 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B25C51001S3 Psaddle12		Acepow LiPo 2S 18.9 Wh. (x2) 7.4v. 25C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>278/301 g.</b>	17.02.14
Shenzhen Acepow Electronics	Gens ace # B50C57002S3 Psaddle12		Acepow LiPo 2S 42.2 Wh. 7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>274/296 g.</b>	17.02.14






**BATTERIES BELOW THIS LEVEL WERE APPROVED BY IFMAR FOR 2013 AND ARE ALLOWED AT 2020 EVENTS.**

**2S LiPo STICK BATTERIES**

Shanghai Dualsky	Track & Field # 33843		Dualsky LiPo 2S 47.0 Wh. 7.4v. 75C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>293/317 g.</b>	14.02.13
Intellect Battery	IP # CC2S7200V8		Intellect LiPo 2S 53.0 Wh. 5mm. Tubes 7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	14.02.13
Intellect Battery	IP # BG2S4600V8		Intellect LiPo 2S 34.0 Wh. 7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/223 g.</b>	14.02.13
LRP VTEC	VTEC # 430205		LRP LiPo 2S 38.5 Wh. Has chassis location. 7.4v. 40C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>242/262 g.</b>	14.02.13
LRP VTEC	VTEC # 430206		LRP LiPo 2S 42.2 Wh. 7.4v. 40C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	14.02.13
LRP VTEC	VTEC # 430201		LRP LiPo 2S 51.8 Wh. 7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>303/328 g.</b>	14.02.13
LRP VTEC	VTEC Big Mama. # 430200		LRP LiPo 2S 53.5 Wh. 7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>311/337 g.</b>	14.02.13
LRP VTEC	VTEC # 430204		LRP LiPo 2S 33.3 Wh. 7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>207/224 g.</b>	14.02.13
Muchmore	Muchmore # MLI- ST4400FD		Muchmore LiPo 2S 32.6 Wh. 7.4v. 70C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>208/226 g.</b>	14.02.13
Nosram VTEC	Nosram X-treme Race # 999505		Nosram LiPo 2S 38.5 Wh. Has chassis location. 7.4v. 40C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>241/261 g.</b>	14.02.13

Nosram VTEC	Nosram X-treme Race # 999506		Nosram LiPo 2S 42.2 Wh.	7.4v. 40C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>284/308 g.</b>	14.02.13
Nosram VTEC	Nosram X-treme Race # 999501		Nosram LiPo 2S 51.8 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>303/328 g.</b>	14.02.13
Nosram VTEC	Nosram X-treme Race Big Mama # 999500		Nosram LiPo 2S 53.5 Wh.	7.4v. 50C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>311/337 g.</b>	14.02.13
Nosram VTEC	Nosram X-treme Race # 999504		Nosram LiPo 2S 33.3 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>207/224 g.</b>	14.02.13
nVision	nVision # NVO 1114		nVision LiPo 2S 59.2 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>301/326 g.</b>	14.02.13
nVision	nVision # NVO 1113		nVision LiPo 2S 59.2 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>301/326 g.</b>	14.02.13
nVision	nVision # NVO 1112		nVision LiPo 2S 29.6 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/223 g.</b>	14.02.13
Tianco	ORCA Infinite # OB7080G5		Tianco LiPo 2S 51.8 Wh. 5mm. Tubes	7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	14.02.13
Tianco	ORCA Infinite # OB45480P4		Tianco LiPo 2S 33.3 Wh.	7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/223 g.</b>	14.02.13
Team ORION	ORION Carbon Pro # ORI 14057		Orion LiPo 2S 59.2 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. with wires allowed: - <b>306/331 g.</b>	14.02.13
Team ORION	ORION Carbon Pro # ORI 14056		Orion LiPo 2S 59.2 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>301/326 g.</b>	14.02.13
Team ORION	ORION Carbon Pro WTS # ORI 14053		Orion LiPo 2S 29.6 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>203/219 g.</b>	14.02.13
Team ORION	ORION Carbon Pro # ORI 14055		Orion LiPo 2S 29.6 Wh.	7.4v. 90C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/223 g.</b>	14.02.13
Protek RC	Protek # PTKLPH5600 2S100P5		Protek LiPo 2S 41.4 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	14.02.13

Protek RC	Protek # PTKLPH7000 2S100P5		Protek LiPo 2S 51.6 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>312/338 g.</b>	14.02.13
Protek RC	Protek # PTKLPH4300 2S100S		Protek LiPo 2S 31.8 Wh.	7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>206/224 g.</b>	14.02.13
Associated Electrics	Reedy # 309		Reedy LiPo 2S 57.0 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>305/331 g.</b>	14.02.13
Associated Electrics	Reedy # 602		Reedy LiPo 2S 31.0 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>200/216 g.</b>	14.02.13
Associated Electrics	Reedy Wolfpack # 736		Reedy LiPo 2S 37.0 Wh.	7.4v. 25C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>254/276 g.</b>	14.02.13
Associated Electrics	Reedy Wolfpack # 738		Reedy LiPo 2S 28.0 Wh.	7.4v. 25C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>199/215 g.</b>	14.02.13
Vapex Technology	VP Racing # VP95057		Vapex LiPo 2S 52.5 Wh.	7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>300/325 g.</b>	14.02.13
Yokomo	Max Power # YBP257BD		Yokomo LiPo 2S 42.2 Wh.	7.4v. 75C.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>283/307 g.</b>	14.02.13
Hacker Motor	Hacker Top Fuel # 76500277		Hacker LiPo 2S 48.1 Wh.	7.4v. 90C.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>296/320 g.</b>	14.02.13
Hacker Motor	Hacker Top Fuel # 7400277		Hacker LiPo 2S 29.6 Wh.	7.4v. 90C.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>205/223 g.</b>	14.02.13
<b>2S LiPo SADDLE BATTERIES</b>						
Shanghai Dualsky	Track & Field # 33864		Dualsky LiPo 2S 39.2 Wh.	7.4v. 70C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>259/281 g.</b>	14.02.13
Intellect Battery	IP # TP2S6000V8		Intellect LiPo 2S 22.0 Wh. (x2)	7.4v. 80C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>274/297 g.</b>	14.02.13
LRP VTEC	VTEC # 430203		LRP LiPo 2S 42.9 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	14.02.13
Nosram VTEC	Nosram X-treme Race # 999503		Nosram LiPo 2S 42.9 Wh.	7.4v. 55C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	14.02.13

Protek RC	Protek # PTKLPH5500 2S100SP		Protek LiPo 2S 41.1 Wh. 7.4v. 100C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>273/295 g.</b>	14.02.13
Associated Electrics	Reedy # 310		Reedy LiPo 2S 21.0 Wh. (x2) 7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>257/278 g.</b>	14.02.13
Associated Electrics	Reedy Wolfpack # 737		Reedy LiPo 2S 18.0 Wh. (x2) 7.4v. 25C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>265/287 g.</b>	14.02.13
Vapex Technology	VP Racing # VP95088		Vapex LiPo 2S 48.0 Wh. 7.4v. 65C	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>280/303 g.</b>	14.02.13
Yokomo	Max Power # YBP259BF		Yokomo LiPo 2S 3.7v.(x2) 21.8 Wh. (x2) 75C.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	14.02.13
Hacker Motor	Hacker Top Fuel # 75000278		Hacker LiPo 2S 40.7 Wh. 7.4v. 90C. Wt. 269/291 g.	Max. dimensions : 139.0 x 47.0 x 25.1 Scrutineers Wt. allowed: - <b>269/291 g.</b>	14.02.13